

Compact Fans - AC



Model	Bearing	Voltage (VAC)	Frequency (Hz)	Current (A)	Speed (RPM)	Power (W)	Air Flow (CFM)	Static Pressure (mm H ₂ O)	Noise (dBA)	Wt. kg
80X80X25mm (Pack size: 50 No's)										
8A115HBAC	Ball	115	50/60	0.210/0.180	2300/2800	14/12	21/25	4/4.8	29/34	12
8A115HSAC	Sleeve	115	50/60	0.210/0.180	2300/2800	14/12	21/25	4/4.8	29/34	12
8A230HBAC	Ball	230	50/60	0.070/0.060	2300/2800	14/12	21/25	4/4.8	29/34	12
8A230HSAC	Sleeve	230	50/60	0.070/0.060	2300/2800	14/12	21/25	4/4.8	29/34	12
92X92X25mm (Pack size: 50 No's)										
9A115HBAC	Ball	115	50/60	0.210/0.180	2300/2800	14/14	36/42	5/6	36/38	15
9A115HSAC	Sleeve	115	50/60	0.210/0.180	2300/2800	14/14	36/42	5/6	36/38	15
9A230HBAC	Ball	230	50/60	0.070/0.060	2300/2800	14/12	36/42	5/6	36/38	15
9A230HSAC	Sleeve	230	50/60	0.070/0.060	2300/2800	14/12	36/42	5/6	36/38	15
120X120X38mm (Pack size: 40 No's)										
12A24HBAC	Ball	24	50/60	1/0.9	2650/2800	18/17	95/102	8.4/9.4	43/46	20
12A24HSAC	Sleeve	24	50/60	1/0.9	2650/2800	18/17	95/102	8.4/9.4	43/46	20
12A115HBAC	Ball	115	50/60	0.200/0.180	2650/2800	14/12	95/102	8.4/9.4	43/46	20
12A115HSAC	Sleeve	115	50/60	0.200/0.180	2650/2800	14/12	95/102	8.4/9.4	43/46	20
12A230HBAC	Ball	230	50/60	0.100/0.090	2650/2800	18/17	95/102	8.4/9.4	43/46	20

Note:

- Weight mentioned is for the pack size.
- Ask for Low Noise versions

Specifications subject to change without notice