

SN03D12-502-M (Order no. 082164)

Series SN... 12 mm, mechanical

- ▶ Plunger spacing 12 mm
- ▶ Upright housing, small flange
- ▶ Degree of protection IP67 according to IEC 60529



Switching element

ES 502 E Snap-action switching contact 1 NC + 1 NO

Technical data

Approvals



Electrical connection values

Fuse	max. 8 A gG	
Connection cross section	0.34 ... 1.5 mm ²	
Rated insulation voltage U _i	250 V	
Rated impulse voltage U _{imp}	2.5 kV	
Utilization category		
	AC-15	6 A 230 V
	DC-13	6 A 24 V
	AC-12	8 A 250 V
Switching current		
	min. at DC 12V	min. 10 mA
thermal rated current I _{th}	8 A	

Mechanical values and environment

Anfahrsgeschwindigkeit	0.01 ... 40 m/min	
Connection type		
	2 x	M20 x 1.5
Number NC contacts	3	
Number of switching elements	3	
Number of NO contacts	3	
Design	upright	
Actuating element	Chisel plunger (Operating point accuracy ± 0.002. The reproducible operating point accuracy refers to the axial travel of the plunger after the switching element ES 502 E has been run-in with approx. 2,000 operating cycles.)	
Actuating force	min. 20 N	
Installation orientation	any	

Storage temperature -25 ... 80 °C

Mechanical life 30 x 10⁶

Switching principle Snap-action switching contact
(Contact closing time<4 Contact bounce time<3)

Degree of protection IP67

Plunger spacing 12 mm

Ambient temperature -5 ... 80 °C

Material

Contact Silver alloy, gold flashed

Housing Die-cast aluminum, anodized

Ordering data

Ordernumber	082164
Item designation	SN03D12-502-M
Gross weight	0,39kg
Global Trade Item Number (GTIN)	4047048003484
Customs tariff number	85365019000
ECLASS	27-27-06-02 Multi-position switch